

**F-Series** 



# Introducing the Epson® SureColor® E6070 (44

EPSON

EPSON

# Introducing the Epson<sup>®</sup> SureColor<sup>®</sup> F6070 (44") and F7070 (64")

How do you reinvent the dye-sublimation transfer printer? You start by specially designing, from the ground up, every component to work together as one system — from the print head and ink technology, to the printer engine and software. The result? A high-performance dye-sublimation transfer printer designed with extreme reliability for true industrial-level production.

Developed using the latest advancements in performance imaging, this innovative system includes our exclusive MicroPiezo® TFP® print head, along with an all-new dye-sublimation ink technology — Epson UltraChrome® DS<sup>1</sup>. The purpose-built SureColor F-Series allows you to focus on what matters most — more profit.

DS	MAXIMUM	MAX. INK CAPACITY	INCLUDED	PRINT SPEEDS <sup>2</sup>	SQ FT/HR
	MEDIA WIDTH	PER COLOR	RIP	High Speed	613
EPSON ULTRACHROME DYE SUB INK	64" AND 44"	1.5 LITERS	WASATCH SOFTRIP®	Production High Quality	301 172

## EPSON SURECOLOR F-SERIES F6070 / F7070

### **Printing Technology**

Advanced MicroPiezo TFP Print Head Variable-Sized Droplet Technology Nozzle Configuration: 720 nozzles per color (x4)

### **Print Direction**

Bi-directional and uni-directional

### **Print Quality**

Maximum Resolution: 720 x 1440 dpi Smallest Droplet Size: 5.3 pl

### New Ink Supply System

Epson UltraChrome DS Ink technology Ink Tank Capacity: 1500 ml Ink Pack Capacity: 1000 ml Cyan, Magenta, Yellow, Black

### **Media Handling**

Paper Feed Method: Friction Auto Take-up Reel Unit: Standard with 64" model Roll OD Dim.: 44" model: Up to 5.9" (3 in. core) 64" model: Up to 9.8" (3 in. core) Roll Core Size: 2" or 3" Roll Weight: Up to 88.18 lbs on 64" model

### **Printable Area**

300 to 1,117 mm (F6070 – 44") 300 to 1,625.6 mm (F7070 – 64") Max. Printing Width: 44" model: 1,112 mm (43.8") 64" model: 1,615 mm (63.6") Margins: 5 mm both sides Media Thickness: Over 75 gsm 44" model: 0.05-0.08 mm 64" model: 0.08-1.00 mm

### **Control Panel**

2.5" Color LCD: 480 x 240 dpi

### **Printer Interfaces**

Hi-Speed USB 2.0, 100BASE-TX/1000BASE-T

### Language

Control Code: Epson ESC/P® raster

### **Environmental Conditions**

Operating: 59 to 95 °F (15 to 35 °C) Recommended: 59 to 77 °F (15 to 25 °C)

### Humidity

Operating: 20 to 80% (40 to 60% recommended)

### Dimensions

F7070: 103"(W) x 50"(D) x 52"(H) Weight: 500 lb F6070: 63"(W) x 32"(D) x 45"(H) Weight: 192 lb

### **Electrical Requirements**

Power Supply: AC 100 – 240 V 50 – 60 Hz 1.0-0.5 A Power Consumption: Operating: Approx. 65 W Ready: Approx. 20 W Standby: Approx. 9 W

### **Acoustic Noise Level**

Approximately 59 dB(A) according to ISO 7779

### **Printer Software**

Communication Driver User and Setup Guides Epson LFP RemotePanel 2 EpsonNet Setup EpsonNet Config EpsonNet PrintOptions

### Front-end RIP Workflow by Wasatch

F6070: Wasatch SoftRip Included F7070: Wasatch SoftRip TX Included

### Epson UltraChrome DS Ink<sup>1</sup>

ink Packs	1000 ml
Black	T741100
Cyan	T741200
Magenta	T741300
Yellow	T741400

**Epson Limited Warranty and Service** Standard one-year on-site

### Accessories

Heavy Roll Media System (Optional on 64") Input / Output roll media diameter Up to 11.8" Input / Output roll media weight Up to 175 lb

# Better Products for a Better Future<sup>®</sup> eco.epson.com

1 The SureColor F-6070 and F-7070 are designed to use only Epson ink packs and not other brands of new or refilled cartridges, or other brands of ink or bulk ink systems. Using Epson cartridges is important for reliable performance and high image quality. Epson offers voluntary recycling of spent ink cartridges.

2 Print speeds are based on print engine speed only. Total throughput times depend upon front-end software, file size, printer resolution, networking, length and width of the print job and frequency of jobs.



Epson America, Inc.: 3840 Kilroy Airport Way, Long Beach, CA 90806 Internet website: www.proimaging.epson.com

**Epson Canada Limited:** 185 Renfrew Drive, Markham, Ontario L3R 6G3 Internet website: **www.proimaging.epson.com** 



EPSON, Epson ESC/P, Epson UltraChrome, MicroPiezo, SureColor and TFP are registered trademarks. EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future is a trademark of Seiko Epson Corporation. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2013 Epson America, Inc. CPD-38723 1/13